

VICTORY POLYCHEM PVT LTD

GAT NO: 399/1-2,PLOT NO 5 ,VILLAGE-BHARE,POST-GHOTAWADE,TALUKA,MULSHI,DISTRICT- PUNE - 412115
Cell No: +91-9850834579,Email: information@polychem.co.in website: www.polychem.co.in

PRODUCT DATA SHEET	
1.IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY	
NAME OF THE PRODUCT	POLYCOOL 86 Conc (Flashing Coolant)
SPECIAL FEATURES	<ul style="list-style-type: none">• POLYCOOL 86 Conc is general-purpose cutting oil with good lubricity. It is blend of lubricant with complex ester, corrosion inhibitors & good antibacterial property.• It is having alkaline pH.• It contains extraordinary antibacterial additives. These additives prevent bacterial growth thereby enhancing coolant life.• It is having an excellent anticorrosive property over a wide dilution range.
DILUTION	<ul style="list-style-type: none">• It is to be used 3 -6 % with water.
APPLICATIONS	<ul style="list-style-type: none">• POLYCOOL 86 Conc is being used as cutting oil for machine operation including Flashing.
TECHNICAL DATA	<ul style="list-style-type: none">• Appearance: - Yellow to Dark Yellow Liquid.• Odour: - Characteristic odour.• Specific Gravity@29.5°C :- 1.0 -1.05• pH of solution :- 10 (+/- 0.5)• Solubility in water: - Soluble.
PACKING & STORAGE	<ul style="list-style-type: none">• 210 LITS PLASTIC BARREL. & Store in a cool, dry, well-ventilated place. Use properly Labeled and closable containers. Avoid direct sunlight, heat sources, and strong oxidizing agents.

SAFETY INFORMATION: - Although this product does not pose a significant hazard to health a good standard of hygiene and housekeeping should be protected when using all type of industrial safety materials. Refer MSDS of the product.